TF1240 Series Dual Spring Stands for Roll-Up Signs

Roll-Up Sign Mounting Options

Adding a clamp to your roll-up sign allows it to be attached to the mast of the TF1240 and the STF1240.

UniClamp

Allows the sign to be affixed to various size square and round masts. Attaches permanently to sign.



Dual Clamp

Features openings for 1" and1-1/4" square masts. Attaches permanently to sign.



Tri-Clamp

Provides dedicated openings for 3/4" and 1" square and 1" round masts. Attaches permanently to sign.



Roll-Up Sign Bracket

The RUB3315 roll-up bracket holds all 36" and 48" roll-up signs with horizontal fiberglass ribs up to 1/4" thick. Attaches to stand.





	Model Number	Sign Height	Roll-Up Sign Holder Type	Legs
	TF1240	Variable	Optional	Aluminum
	STF1240	Variable	Optional	Steel

- TwinFlex™ TF1240 and STF1240 stands meet MUTCD specifications and are NCHRP-350 compliant.
- Displays both 36" and 48" roll-up signs. Maximum display height: 95" to the top of a 48" sign.
- Heavy duty $\mathsf{TwinFlex}^\mathsf{TM}$ dual spring system flexes in windy conditions for stability.
- Springs are treated with a special E-coating industrial finish for long lasting, corrosion-free performance.
- The base is powder coated steel.
- TF1240 legs are aircraft quality aluminum, STF1240 legs are orange powder coated steel. Foot actuated releases provide quick set-up and tear-down. Two position leg height adjustment allows deployment on uneven terrain and anti-skid rubber foot pads help keep stands in place.
- Telescopic mast with 1" square top section allows the use of many types of roll-up sign clamps and brackets.
- Mounted flagholder will hold three standard warning flags.
- Storage size: 6-1/2" x 6-1/2" x 64-1/2". Open footprint: 53" x 74". Max. open height (ground to top of mast): 105".
- Weight: TF1240 30#, STF1240 34#
- TF1240 (2 stage mast) replaces model TF1230 (3 stage mast).
- STF1240 (2 stage mast) replaces STF1230 (3 stage mast).